This Page Is Inserted by IFW Operations and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

•

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 25 April 2002 (25.04.2002)

PCT

(10) International Publication Number WO 02/33879 A2

(51) International Patent Classification7:

H04L 9/00

(21) International Application Number: PCT/EP01/11888

(22) International Filing Date: 15 October 2001 (15.10.2001)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0025435.9 60/242,451 17 October 2000 (17.10.2000) GB 24 October 2000 (24.10.2000) US

(71) Applicant ifor all designated States except US): TELE-FONAKTIEBOLAGET L M ERICSSON (PUBL) [SE/SE]; S-126 25 Stockholm (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): ANDERSON, Stefan [SE/SE]; Koltrastgränd 23, S-230 41 Klägerup (SE).

(74) Agent: O'CONNELL, David, Christopher; Haseltine Lake & Co., Imperial House, 15-19 Kingsway, London WC2B 1UD (GB). (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

 without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SECURITY SYSTEM



(57) Abstract: A communications device, which has a cryptographic module for use in mobile communications, can be used as a cryptographic services provider. For example, the device may be a device which can operate under the Wireless Application Protocol, that is, a WAP-enabled device, such as a mobile phone. This has the advantage that WAP-enabled devices include components which are used in public key/private key cryptographic systems as a part of their standard communication functions. These components therefore advantageously allow the device to be used as a cryptographic services provider. Advantageously, the device can use Wireless Transport Layer Security (WTLS) for mobile communications, and employs its cryptographic module when in use as a cryptographic services provider.

12/33879 A2

WO 02/33879

PCT/EP01/11888

SECURITY SYSTEM

5

15

20

25

30

35

TECHNICAL FIELD OF THE INVENTION

This invention relates to computer systems, and in particular to the improvement of security in such systems. More specifically, the invention relates to a method for improving the security of communications, for example over a computer network, although it is also applicable to increasing the security of a computer system.

-1-

10 BACKGROUND OF THE INVENTION

US-5,689,565 describes a cryptography system architecture for a computer, which provides cryptographic functionality to support an application which requires cryptography. The cryptography system has a cryptographic application program interface (CAPI) which interfaces with the application to receive requests for cryptographic functions. The system further includes at least one cryptographic service provider (CSP) that is independent from, but dynamically accessible by, the CAPI. The CSP provides the cryptographic functionality and manages the secret cryptographic keys.

This system architecture is used in many applications in which data may desirably be transferred across unsecured computer networks such as the internet. For example, this architecture can be used in applications such as email clients, web browsers, etc. A similar architecture can be used for access control within a computer system, and for hard disc encryption.

US-6,038,551 describes a development of the architecture disclosed in US-5,689,565, in which the computer includes a card reader, and an integrated circuit card (IC card) stores the cryptographic keys used by the CSP in the computer, and can perform

10

15

20

25

30

35

is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

BRIEF DESCRIPTION OF DRAWINGS

Figure 1 is a block schematic diagram of a first system implementing the present invention.

Figure 2 is a flow chart showing the operation of the system of Figure 1.

Figure 3 is a flow chart showing in more detail a part of the operation illustrated in Figure 2.

Figure 4 is a block schematic diagram of a second system implementing the present invention.

Figure 5 is a block schematic diagram of a third system implementing the present invention.

Figure 6 is a flow chart showing the operation of the system of Figure 5.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Figure 1 is a block schematic diagram of a computer system, including a personal computer (PC) 10, only the relevant components of which are shown. It will be apparent that, in this embodiment of the invention, and in the other illustrated embodiments, any computer system can be used in exactly the same way as the PC 10.

The computer has a connection to an external network 12, for example through a modem (not shown). Of particular concern here is the situation where the computer 10 is connected to an unsecured network, such as the internet.

The computer 10 has various software applications which require external communication, such as an email application 14, and a web browser 16, which use Secure Socket Layer (SSL) and/or Transport Layer Security (TLS) security. In many cases, the information which

WO 02/33879

5

10

15

20

25

30

35

Transport Layer Security (WTLS) can be used. This provides confidentiality for users, by encrypting messages which are transmitted over the wireless interface, and also provides authentication, by means of digital certificates.

In order to provide this WTLS functionality, the WAP-enabled device 30 includes a cryptographic module, which uses an embedded public key and private key on handshake for authentication, then generates symmetric session keys, which are used to encode messages before transmission and to decode received messages.

For example, the phone 30 may also include a Subscriber Identity Module - Wireless Identity Module (SIM-WIM) card 32, which is used to identify the subscriber, and can contain the cryptographic module. Alternatively, the cryptographic module can be realised in hardware or in software 34 in the phone 30, or may be provided on an external smart card. In order to access the cryptographic module, the MS 30 includes a security manager module 38. The operation of these devices will be explained further below.

In accordance with preferred embodiments of the present invention, the cryptographic module of the phone, and other features which are used to provide secure communication using the Wireless Application Protocol, also allow the phone 30 to be provide some or all of the functionality of a cryptography service provider.

In the case where the cryptographic module is embodied in hardware, the necessary information is provided on an integrated circuit in the device.

Where the Wireless Public Key Infrastructure (WPKI) is used to distribute the parameters for WTLS, it can also be used to distribute the parameters required for use as a cryptography service provider.

5

10

15

20

25

30

35

provider and the MS are possible.

Figure 2 is a flow chart showing a method by which the PC 10 can use the cryptographic functionality in the mobile phone 30.

The procedure starts with step 100, in which the application in the PC 10, such as the email application 14 or web browser 16 determines that cryptographic functionality is required, and sends a command to the CAPI 18. The cryptographic functionality which is required may for example be encryption, decryption, hash generation, message signing, verification, key generation, certificate management, or random number generation. Other types of cryptographic functionality which may be provided are described in the PKCS#11 standard mentioned above.

In step 102, the CAPI selects an appropriate CSP to provide the cryptography function. In this case, the CAPI selects the CSP* 26, which can access the cryptographic module in the MS 30.

In step 104, the CAPI 18 establishes communication with the selected CSP* 26, and the CSP* 26 establishes communications with the MS 30. As discussed above, the communications between the PC 10 and MS 30 can advantageously be over a Bluetooth short range radio link.

In step 106, the operating system (CS) 20 verifies the authenticity of the CSP*. It will be noted that this step may be unnecessary if the authenticity of the CSP* has already been established as part of an earlier process. As an alternative, this step can be carried out earlier in the process, and other changes in the order of the illustrated steps are also possible.

In step 108, a message is passed from the CAPI 18 via the CSP* 26 to the MS 30, with details of the cryptographic operation which is required.

10

15

20

25

30

35

communication.with the hard disc 52. Since the information which is stored on the hard disc may be confidential, the application restricts access thereto, so that only authorised persons can gain access to it.

As is conventional, therefore, the hard disc application 50 can call a cryptographic application program interface (CAPI) 18, which is provided on top of the operating system (OS) 20.

As is also conventional, the cryptographic application program interface (CAPI) 13 can access one or more cryptography service providers (CSPs) 22, 24.

Different cryptography service providers (CSPs) may, for example, use different cryptographic algorithms, and may be used for different purposes.

In accordance with the present invention, as described in more detail with reference to Figures 1-3, some or all of the functionality of a cryptography service provider is available on a separate device, namely a mobile station (MS) 30, and the CSP* 26 can call the required functionality from the MS 30.

The mobile station may be exactly as described with reference to Figures 1 and 3 above.

Figure 5 shows a further alternative system in accordance with the invention.

Again, the computer system is described with reference to a personal computer (PC) 60, but it will be apparent that any computer system can be used in exactly the same way as the PC 60.

The computer has a connection to an external network 12, for example through a modem (not shown) to an unsecured network, such as the internet.

The computer 60 has various software applications which require external communication, such as an email application 14, and a web browser 16, which use Secure Socket Layer (SSL) and/or Transport Layer Security

20

15

20

25

30

35

the Bluetooth short-range radio transmission protocol, although an infrared connection is also possible. The protocol for the connection can for example be based on AT commands, and provides security for those communications. The command set is advantageously a version of the command set defined in a standard such as PKCS#11, described in the document "PKCS#11 v2.10: Cryptographic Token Interface Standard", published by RSA Security Inc. and incorporated herein by reference, where the commands are redefined as AT commands.

Figure 6 is a flow chart showing a method by which the PC 60 can use the cryptographic functionality in the mobile phone 30.

The procedure starts with step 160, in which the application in the PC 60, such as the email application 14 or web browser 16 determines that cryptographic functionality is required, and sends a command to the PKCS#11 interface 70. The cryptographic functionality which is required may for example be encryption, decryption, hash generation, message signing, verification, key generation, certificate management or random number generation.

In step 162, the PKCS#11 interface 70 selects an appropriate CT to provide the cryptography function. In this case, the PKCS#11 interface 70 selects the CT* 76, which can access the cryptographic module in the MS 30.

In step 164, the PKCS#11 interface 70 establishes communication between the application and the selected CT* 76, and the CT* 76 establishes communications with the MS 30. As discussed above, the communications between the PC 60 and MS 30 can advantageously be over a Bluetooth short range radio link.

In step 166, a message is passed from the PKCS#11 interface 70 to the MS 30, calling the cryptographic

CLAIMS

5

10

15

20

25

30

35

- 1. A method of encrypting communications from a computer having an application program interface, the method comprising using a mobile communications device, which includes a cryptographic module for use in mobile communication, as a cryptographic service provider.
- 2. A method as claimed in claim 1, wherein the mobile communications device is a WAP-enabled device.
- 3. A method as claimed in claim 1 or 2, wherein the cryptographic module is that used by the mobile communications device for Wireless Transport Layer Security communications.
- 4. A method as claimed in claim 1, 2 or 3, comprising providing a wired connection between the mobile communications device and the computer.
- 5. A method as claimed in claim 1, 2 or 3, comprising providing a wireless connection between the mobile communications device and the computer.
- 6. A method as claimed in any of claims 1 to 5, comprising:

when the application program interface requires cryptographic functionality, calling a cryptographic service provider function in the mobile communications device.

- 7. A mobile communications device, comprising a cryptographic module, the cryptographic module being usable:
- (a) for encoding wireless communications from the device;
- (b) in a cryptographic service provider with an application program interface of a remote computer.
- 8. A mobile communications device as claimed in claim 7, having a short-range wireless communications transceiver, for sending signals to and receiving signals from the remote computer.

to said command.

5

10

15

20

25

30

35

- 19. A module for a personal computer, wherein, in response to the module receiving a first command from a cryptographic application program interface, indicating that it requires cryptographic functionality, the module sends a second command to a mobile communication device, such that the mobile communications device acts as a cryptographic service provider for said personal computer.
- 20. A method of encrypting computer communications, the method comprising using a separate mobile communications device, which includes a cryptographic module for use in mobile communication, as a cryptographic service provider.
 - 21. A method as claimed in claim 20, wherein the mobile communications device is a WAP-enabled device.
 - 22. A method as claimed in claim 20 or 21, wherein the cryptographic module is that used by the mobile communications device for Wireless Transport Layer Security communications.
 - 23. A method as claimed in claim 20, 21 or 22, comprising providing a wireless connection between the mobile communications device and the computer.
 - 24. A computer system, comprising:

a computer; and

a mobile communications device, including a cryptographic module,

the computer having at least one application which requires cryptographic functionality,

a first part of the required cryptographic functionality being provided in the computer, and a second part of the required cryptographic functionality being provided in the mobile communications device,

the computer and the mobile communications device having means for establishing a secure communications

10

15

20

25

30

35

device.

- 32. A method as claimed in claim 28, comprising using a cryptographic module realised in hardware in the mobile communications device.
- 33. A method as claimed in claim 28, comprising using a cryptographic module realised in software in the mobile communications device.
- 34. A method as claimed in claim 28, comprising using a cryptographic module provided on an external smart card which can be read by the mobile communications device.
- 35. A method as claimed in claim 28, comprising using a cryptographic module a Wireless Identity Module (WIM) card in said mobile communications device.
- 36. A computer system for supporting an application, the computer system comprising:
 - a cryptographic application program interface; and a cryptography service provider,

wherein, when the cryptographic application program interface determines that the application requires cryptographic functionality, sends a command to the cryptography service provider, and

wherein the cryptography service provider has a communications link to a cryptographic module of a mobile communications device, the cryptographic module of the mobile communications device being usable to encrypt communications between the mobile communications device and a telecommunications network over a wireless interface, and

wherein the cryptography service provider can obtain the cryptographic functionality, required by the application, from the cryptographic module of the mobile communications device.

37. A system as claimed in claim 36, wherein the cryptographic module is realised in hardware in the

5

15

20

25

30

mobile communications device further comprising a security manager module for receiving commands from a computer system over a second interface, wherein, in response to suitable commands received from the computer system over the second interface, the security manager module requests a cryptographic function from the cryptographic module, and returns the results of the cryptographic function to the computer system over the second interface.


- 10 45. A mobile communications device as claimed in claim 44, wherein the security manager module responds to a command set defined in a standard PKCS#11, where the commands are redefined as AT commands.
 - 46. A mobile communications device as claimed in claim 44, wherein the second interface is a Bluetooth short-range radio interface.
 - 47. A module for a computer system, the module comprising:


an application interface for connection to a computer application; and


an external interface for connection to a mobile communication device containing a cryptographic module;


wherein, when the module receives from the application interface a request for a cryptographic function which the module is unable to provide, the module sends a command over the external interface to the mobile communications device to request the cryptographic function therefrom.


- 48. A module for a computer system as claimed in claim 47, wherein the module has some cryptographic functionality, and comprises means for determining in response to a request from the application interface whether it is able to provide the requested function cryptographic function.
- 35 49. A module for a computer system as claimed in














PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference	FOR FURTHER see Notification of Transmittal of International Search Report				
HL76380/006	ACTION (Form PC1/ISA/220) as well as, where applicable, item 5 below.				
International application No.	International filing date (day/month/year)	(Earliest) Priority Date (day/month/year)			
PCT/EP 01/11888	15/10/2001	17/10/2000			
Applicant		11112000			
TELEFONAKTIEBOLAGET L M EF	RICSSON (PUBL)				
	,	nority and is transmitted to the applicant			
This International Search Report consists of	of a total of sheets.				
[A] It is also accompanied by a	copy of each prior art document cited in this	report.			
Basis of the report					
	ternational search was carried out on the bas ss otherwise indicated under this Item.	• •			
, , ,	s carried out on the basis of a translation of th				
b. With regard to any nucleotide and was carried out on the basis of the	or amino acid sequence disclosed in the integration of the integration	ernational application, the international search			
	al application in written form.				
filed together with the intern	ational application in computer readable form.				
furnished subsequently to the					
	is Authority in computer readble form.				
- and the application as t		* 4			
the statement that the inform furnished	nation recorded in computer readable form is i	identical to the written sequence listing has been			
2. Certain claims were found	unsearchable (See Box I).				
3. Unity of invention is lacking	g (see Box II).				
4. With regard to the title,					
the text is approved as subm	nitted by the applicant.				
_	d by this Authority to read as follows:				
5. With regard to the abstract,					
the text is approved as subm	itted by the applicant				
the text has been established	t, according to Rule 38.2(b), by this Authority at the of mailing of this international search report	as It appears in Box III. The applicant may, t, submit comments to this Authority.			
6. The figure of the drawings to be published	ed with the abstract is Figure No.	1			
as suggested by the applican		None of the figures.			
because the applicant failed to	to suggest a figure.				
because this figure better cha	aracterizes the Invention.				

INTERNATIONAL SEARCH REPORT

International Application No PCT/EP 01/11888

A. CLASSIF	TICATION OF SUBJECT MATTER H04L29/06 H04Q7/38				
According to	International Patent Classification (IPC) or to both national classifica	tion and IPC			
B. FIELDS	SEARCHED	and a support			
Minimum do	cumentation searched (classification system followed by classification H04L H04Q	n symbols)			
	on searched other than minimum documentation to the extent that su	uch documents are included in the fields sea	rched		
Documentati	on searched other than minimum documentation to the extent that sa				
Electronic da	ata base consulted during the international search (name of data base	se and, where practical, search terms used)			
EPO-In	ternal				
	•		·		
	ENTS CONSIDERED TO BE RELEVANT	nyant passages	Relevant to claim No.		
Category *	Citation of document, with indication, where appropriate, of the rele	evani passages	neievala to dalli ivo.		
Α	WO 00 02406 A (NOKIA NETWORKS OY JAN ERIK (FI)) 13 January 2000 (2000-01-13) page 2, line 21 -page 3, line 4	; EKBERG	1-50		
Α	WO 00 20972 A (L 3 COMM CORP) 13 April 2000 (2000-04-13) abstract; claim 1		1–50		
Α .	US 5 878 142 A (AMORUSO VICTOR P 2 March 1999 (1999-03-02) column 2, line 21 - line 54	ET AL)	1-50		
Furth	ner documents are listed in the continuation of box C.	χ Patent family members are listed in	annex.		
Special ca	tegories of cited documents:	*T* later document published after the Intern	ational filing date		
'A' docume	ent defining the general state of the art which is not ered to be of particular relevance	or priority date and not in conflict with the cited to understand the principle or theo	e application but		
'E' earlier o	considered to be of particular relevance invention 'E' earlier document but published on or after the international filling date 'x' document of particular relevance; the claimed invention cannot be considered to				
"L" document which may throw doubts on priority claim(s) or involve an inventive step when the document is taken alone which is cited to establish the publication date of another 'Y' document of particular relevance; the claimed invention					
1	ent referring to an oral disclosure, use, exhibition or	cannot be considered to involve an inve document is combined with one or more ments, such combination being obvious	other such docu-		
P docume	ent published orior to the international filing date but	in the art. *&* document member of the same patent fa	mity		
Date of the	actual completion of the international search	Date of mailing of the international sear	ch report		
2	6 July 2002	05/08/2002			
Name and	nailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2	Authorized officer			
	NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Veen, G			

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/EP 01/11888

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
WO 0002406	Α	13-01-2000	FI AU DE WO GB	981565 A 4912199 A 19983405 TO 0002406 A2 2355157 A	08-01-2000 24-01-2000 31-05-2001 13-01-2000 11-04-2001
WO 0020972	A	13-04-2000	US AU EP WO	6151677 A 6292999 A 1149343 A2 0020972 A2	21-11-2000 26-04-2000 31-10-2001 13-04-2000
US 5878142	Α	02-03-1999	US US	5546463 A 5778071 A	13-08-1996 07-07-1998